



The EVO TP4 Tru-Flat TouchPC by POS-X sets a whole new standard by offering enterprise class build quality, the latest in fanless dual core processing, and Tru-Flat touch screen technology. The TP4's sturdy aluminum alloy frame acts as a large heatsink, making fanless dual-core performance possible. Achieving an IP54 certified rating, the TP4 is both dust and splash resistant.




- 15" Tru-Flat Zero Bezel Touchscreen
- Truly fanless design supports dual core processing
- Built in cable management keeps cords out of site
- EZHD Slot makes for quick HDD or SSD replacement
- IP54 Rating Resistant to dust buildup and splashing water
- Die-cut aluminum alloy frame provides bump-free operation
- 3-year Warranty include 2-day Advance Exchange service

Datapoint POS



EVO TruFlat TouchPC Specifications

PART NUMBER	EVO-TP4C
MOTHERBOARD	C48
CPU	Intel® Atom D525 1.8Ghz Dual Core Procesor
Chip Set	CPU with Graphic built-in + ICH 8M
System Memory	1-4 GB DDR III
Video	Integrated Intel® GMA® 3150 Graphics Engine 256 MB Shared Video
PORTS	
Parallel	1 x Parallel Port
USB	4 x USB2
Serial	4 xRJ 45 COM (Com1, Com2, Com3 RS232 Com4 with 5V/12V)
LAN	1–10/100/1000 baseT LAN
VGA	1 x Additional VGA Port
Cash Drawer Port	1 x RJ11 (12V/24V cash drawer)
Speakers	2 x 2W
HARD DRIVE	2.5" Easy Access Slot: 250GB+ HDD, 16GB-60GB+ SSD
PHYSICAL	
Housing	Die Cut Aluminum
Weight with Base	15.4 lbs
Dimensions with Base	14.21" (W) x 9.76" (D) x 13.27" (H)
VESA Wall Mountable	100mm x 100mm
Tilt Angle	0° to 90°
Housing Color	Black
Bezel	No Bezel
LCD Display	15" 1024 x 768 pixel, 16.7M colors 250 nit
Touch Screen	5-Wire Resistive, 35+ millions taps per location
ELECTRICAL	Ext. 90W 19V 4.74 A
ENVIRONMENTAL	
Ingress Protection Rating	IP54 - Resistant to dust buildup and splashing water
Temperature	41°F to 95°F operating
Humidity	20%-80% non-condensing
WARRANTY	3-year includes 2-day Advance Exchange service
CERTIFICATIONS	FCC, Class A, CE, LVD, RoHs
OPERATING SYSTEM	None/ WIN 2000/XP/XP Embedded/POSReady 2009/VISTA/Linux/ Windows 7
-	·



ACCESSORIES	
EVO-MR4	3 Track MSR
EVO-RD4-VFD	Integrated Customer Display
EVO-RD4-LCD8	Integrated Rear Display, 8.4" LCD, VGA
EVO-BR4	Integrated Bio Reader
EVO-XZ4-M100	Universal VESA Mount for All TouchPC & Touch Monitors

POS-X, Inc. 1975 Midway Lane Suite O Bellingham, WA 98226 www.pos-x.com sales@pos-x.com tel 1.800.790.8657 fax 360.738.3495